



Door Edge Protection Film (PN 08582 & PN 08583)

DIRECTIONS FOR USE

Important: Please read all instructions before beginning.

PN 08582 Contains two 36 inch Door Edge Protection Film strips for most sedans.

PN 08583 Contains two 42 inch Door Edge Protection Film strips for most trucks and SUVs

NOTE: If the door edge has existing chips that have begun to rust, there is the potential for paint lifting upon removal of Door Edge Protection Film.

NOTE: If chips exist, it is recommended to apply touch-up paint before applying Door Edge Protection Film to protect against rust. Follow the paint manufacturer's instructions for dry times.

1. Wash your hands thoroughly as dirt and skin oils show up easily on the adhesive and are difficult to remove. Avoid application in windy conditions as dust or other debris may attach to adhesive.
2. Clean the door edge on both the interior and exterior surfaces using 3M Car Wash Soap, rinse with water and dry with a microfiber towel. Apply only to a clean surface free of wax, grease, and dirt, between 55°–90°F.



3. Always check part position, shape and size before applying. The Door Edge film is rounded on the ends; if desired it can be cut straight.



4. Start to remove one strip from the paper. Do not pull the entire strip off the paper as the adhesive can become contaminated.
5. Beginning at the top, press the film onto the door's exterior surface so that half of the film width is on the outside door edge, and half is extending beyond the door edge.



6. Continue this process down the door edge to the bottom of the film. Trim at the bottom as necessary with scissors or razor blade.

NOTE: Use caution with cutting tools, as sharp blades can cause serious injury or harm paint. Follow manufacturer's instructions for each cutting tool used.



7. Begin pressing the film around the edge of the door over the entire length of the door, but not all the way to the back side yet. This will help to prevent air bubbles.



8. After starting to secure the edge, continue to fold the film around to the back of the door edge over the entire length of the door.



9. Remove all air bubbles by smoothing with moderate finger pressure.
10. Repeat steps 5 – 9 on second door.

NOTE: Do NOT wash vehicle for 24 hours after film application. Wash and wax as normal after 24 hours.

Removal: Begin removal on the inside door edge at the top and pull the strip outward slowly, keeping the strip stretched and perpendicular to the door to release the adhesive.

Try these other great 3M solutions to restore the look and performance of any car.

3M™ Scratch Removal System

PN 39071



Nobody likes those unsightly scratches that appear when tree branches, boxes, fingernails or sports equipment touch their car. Now those light scratches can be removed using the 3M™ Scratch Removal System PN 39071. This kit uses the same technology as the 3M headlight solution kits, making it easy to use and very effective: Light scratches will disappear! Available in select retailers and at Shop3M.com.

3M™ Headlight Lens Solutions

PN 39008, 39014, 39045



The 3M Headlight Lens Solutions are designed to restore clarity to headlight lenses that have become yellowed, cloudy, or hazed over time. By restoring clarity to the lens you improve the performance of the headlight and enhance the appearance of the vehicle. Available in select retailers and at Shop3M.com.

Paint Protection Film for Hood, Fenders, Mirrors, etc.



Looking to add more paint protection film to a vehicle? Allow a 3M Certified Installer to install paint protection film to vulnerable surfaces such as door cups, fenders, mirrors, hood, etc... to protect against chips, scratches, and scuffs. You can learn more and find an installer at www.3M.com/paintprotectionfilm.com.

Warranty, Limited Remedy, and Disclaimer: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M Automotive Aftermarket Division

3M Center/Bldg. 223-6N-01
St. Paul, MN 55144-1000
1-877-MMM-CARS (666-2277)
www.3MCarCare.com

3M is a trademark of 3M Company.

Made in the USA with US and globally sourced materials.

© 3M 2011. All rights reserved. 34-8707-6957-6